

One-Shot® 15W 100V 200mm (8") Twin Cone Fire/Evac (EWIS)

SPECIFICATIONS

Speaker driver: C 2118B
 Power taps: 1.25, 2.5, 5, 10, 15 watts
 SPL 1W @ 1m 92dB @ 1kHz ±2dB
 Freq response: 100Hz - 15kHz
 Terminal type: 4 way screw terminal block & 22µF bipolar capacitor
 Ceiling cutout: 246mm Ø
 Transformer cover: No
 Cable restraint: No



Price Each	RRP	4+	10+
C 2136 White	59.00	54.00	46.00

One-Shot® 15W 100V 200mm (8") Coaxial 2-Way Fire/Evac (EWIS)

SPECIFICATIONS

Speaker driver: C 2120A
 Power taps: 1.25, 2.5, 5, 10, 15 watts
 SPL 1W @ 1m 90dB @ 1kHz ±2dB
 Freq response: 45Hz - 20kHz
 Terminal type: 4 way screw terminal block & 22µF bipolar capacitor
 Ceiling cutout: 246mm Ø
 Transformer cover: No
 Cable restraint: No



Price Each	RRP	4+	10+
C 2138 White	95.00	88.00	79.00

One-Shot® 15W 100V 200mm (8") Twin Cone Fire/Evac (EWIS)

SPECIFICATIONS

Speaker driver: C 2117A
 Power taps: 1.25, 2.5, 5, 10, 15 watts
 SPL 1W @ 1m 95dB @ 1kHz ±2dB
 Freq response: 55Hz - 15kHz
 Terminal type: 4 way screw terminal block & 22µF bipolar capacitor
 Ceiling cutout: 246mm Ø



Price Each	RRP	4+	10+
C 2142 White	79.00	72.00	69.00

One-Shot® 8 Ohm Coaxial 2-Way 200mm (8")

SPECIFICATIONS

Speaker driver: C 2005
 Power rating: 50 watts
 SPL 1W @ 1m 90dB @ 1kHz ±3dB
 Freq response: 50Hz - 20kHz
 Terminal type: Solder tags
 Ceiling cutout: 246mm Ø



Price Each	RRP	4+	10+
C 2130 White	65.00	58.00	52.00

One-Shot® 8 Ohm Twin Cone 200mm (8")

SPECIFICATIONS

Speaker driver: C 2000A
 Power rating: 10 watts
 SPL 1W @ 1m 92dB @ 1kHz ±2dB
 Freq response: 80Hz - 18kHz
 Terminal type: Solder tags
 Ceiling cutout: 246mm Ø



Price Each	RRP	4+	10+
C 2140 White	29.95	27.50	25.00

One-Shot® 8 Ohm Coaxial 2-Way 100mm (4")

SPECIFICATIONS

Speaker driver: C 0645
 Power rating: 10 watts
 SPL 1W @ 1m 87dB @ 1kHz ±2dB
 Freq response: 80Hz - 20kHz
 Terminal type: Solder tags
 Ceiling cutout: 140mm Ø



Price Each	RRP	4+	10+
C 2144 White	39.00	36.00	30.00

AS ISO7240.24 One-Shot® Fire Speaker Range

This range of speakers have been engineered to meet the requirements of evacuation and occupant warning paging systems. The high efficiency speaker and transformer combination ensures high SPL, wide frequency response, superior speech intelligibility and reproduction for mission critical applications. All components of the fixture are manufactured from high quality, long lasting, flame retardant material and tested to the rigours of the new standard. On site installation will be simple and straight forward. Oversized cable glands and terminal blocks will make on site termination easier than other competing products. Finally the speaker will just 'snap fit' into the ceiling. Far easier than competitors models being offered on the market!

The One-Shot 'rat trap' uses an ingenious patented spring mechanism that snaps like a rat trap when activated. Includes three retaining clips ensuring the grille fits snugly to the ceiling without sagging or drooping. Even with the new speaker cover we have kept overall weight at just 700 grams ensuring a neat finish even in soft tile ceilings. **The Redback® One-Shot is a patented and registered design.** For best results we recommend using the T 2312A holesaw.



One-Shot® Metal 100mm (4") Low Profile Flush Mnt Fire Speaker



Patent pending.

Approved for AS ISO7240.24:2015 installations. Our first One-Shot speaker with a metal grille, this model has been designed for installations requiring a premium finish whilst still meeting the required fire standards. They can also be used for standard 100V PA/BGM installations. These models are ideal for low profile ceiling spaces. They feature flame retardent housing material, sealed cable gland entries and a tuned PA driver to suit the new approval requirements.

Price Each	RRP	4+	10+
C 2260 White Metal Grille 5W	85.00	80.00	75.00
C 2261 Black Metal Grille 5W	90.00	85.00	80.00

One-Shot® 100V 100mm (4") Low Profile Flush Mnt Fire Speaker



Patent pending.

Approved for AS ISO7240.24:2015 installations. A lower profile version of the C 2170. These models are ideal for low profile ceiling spaces. They feature flame retardent housing material, sealed cable gland entries and a tuned PA driver to suit the new approval requirements.

Price Each	RRP	4+	10+
C 2160 White 5W	80.00	75.00	70.00
C 2161 Black 5W	85.00	80.00	75.00