

### One-Shot® Surface Mount PA Speakers

Super Fast Installation. Save Time & Money!

The innovative One-Shot range is moulded from industrial grade polypropylene and designed to mount directly to the underside of concrete slabs or inaccessible ceilings. The housing is surface mounted with concealed internal fixings. Cable entry is from the rear, or via surface mounted conduit (4 x 19mm conduit knockouts provided). Ideal for use in plant rooms, warehouses, shopping centres, malls etc.

Registered design



1. Fit the surface mounting ring.



2. Terminate the speaker.



3. Snap the grille into the mounting ring.

### One-Shot® 5W 100V 100mm (4") Twin Cone

Simply snap-fit in seconds to the surface mounting ring, reducing installation time considerably. The C 0699 adaptor plate enables the surface mounting ring to be fixed to a standard conduit junction box without the need for drilling into the concrete slab.

**SPECIFICATIONS**

Speaker driver: C 2103A  
 Power taps: 0.33, 0.66, 1.25, 2.5, 5 watts  
 SPL 1W @ 1m: 90dB @ 1kHz ±2dB  
 Freq response: 100Hz - 15kHz  
 Terminal type: 4 way screw terminal & 22µF bipolar cap  
 Transformer cover: Yes  
 Cable restraint: No



C 0699 fitted to mounting ring.

Price Each	RRP	4+	10+
<b>C 0703</b> White	<b>60.00</b>	<b>54.00</b>	<b>50.00</b>
<b>C 0704</b> Black	<b>65.00</b>	<b>60.00</b>	<b>55.00</b>
<b>C 0699</b> Adaptor plate for conduit boxes	<b>4.60</b>	<b>4.20</b>	<b>3.70</b>

### One-Shot® 5W 100V 100mm (4") Fire Speaker

**Approved for AS ISO7240.24:2015 installations.** Fire version of our popular One-Shot C 0703 speaker. It features flame retardant housing material and a tuned PA driver to suit the new approval requirements. One-Shot design simply snap-fits in seconds to the surface mounting ring, reducing installation time considerably. The C 0699 adaptor plate enables the surface mounting ring to be fixed to a standard conduit junction box without the need for drilling into the slab.



**SPECIFICATIONS**

Power taps: 0.33, 0.66, 1.25, 2.5, 5W  
 SPL 1W @ 1m: 90dB @ 1kHz ±2dB  
 Freq response: 100Hz - 15kHz  
 Size: 220Ø x 55mm  
 Terminal type: 4 way screw terminal & 22µF bipolar cap  
 Flame retardant cover: Yes  
 Cable restraint: Yes

Price Each	RRP	4+	10+
<b>CF0703</b> White	<b>70.00</b>	<b>65.00</b>	<b>58.50</b>
<b>CF0704</b> Black	<b>77.00</b>	<b>71.50</b>	<b>64.35</b>
<b>C 0699</b> Adaptor plate for conduit boxes	<b>4.60</b>	<b>4.20</b>	<b>3.70</b>

### One-Shot® 5W 100V 200mm (8") Twin Cone

Simply snap-fit in seconds to the surface mounting ring, reducing installation time considerably. The C 0713 adaptor plate enables the surface mounting ring to be fixed to a standard conduit junction box without the need for drilling into the concrete slab.

**SPECIFICATIONS**

Speaker driver: C 2112C  
 Power taps: 0.33, 0.66, 1.25, 2.5, 5 watts  
 SPL 1W @ 1m: 93dB @ 1kHz ±2dB  
 Freq response: 75Hz - 15kHz  
 Terminal type: 4 way screw terminal & 22µF bipolar cap  
 Transformer cover: Yes  
 Cable restraint: Yes



C 0713 fitted to mounting ring.

Price Each	RRP	4+	10+
<b>C 0715</b> White	<b>69.00</b>	<b>65.00</b>	<b>59.00</b>
<b>C 0716</b> Black	<b>75.00</b>	<b>69.00</b>	<b>64.00</b>
<b>C 0713</b> Adaptor plate for conduit boxes	<b>9.50</b>	<b>8.70</b>	<b>7.65</b>

### One-Shot® 15W 100V 200mm (8") Twin Cone

**High power model utilising the C 2117A PA driver.** Simply snap-fit in seconds to the surface mounting ring, reducing installation time. The C 0713 adaptor plate enables the surface mounting ring to be fixed to a standard conduit junction box without the need for drilling into the concrete slab.

**SPECIFICATIONS**

Speaker driver: C 2117A  
 Power taps: 1.25, 2.5, 5, 10, 15 watts  
 SPL 1W @ 1m: 95dB @ 1kHz ±2dB  
 Freq response: 80Hz - 12kHz



Terminal type: 4 way screw terminal & 22µF bipolar cap  
 Transformer cover: No  
 Cable restraint: No

Price Each	RRP	4+	10+
<b>C 0720</b> White	<b>95.00</b>	<b>85.00</b>	<b>72.50</b>
<b>C 0721</b> Black	<b>100.00</b>	<b>90.00</b>	<b>75.00</b>
<b>C 0713</b> Adaptor plate for conduit boxes	<b>9.50</b>	<b>8.70</b>	<b>7.65</b>

### One-Shot® 5W 100V 200mm (8") Fire Speakers

**Approved for AS ISO7240.24:2015 installations.** Fire versions of our popular One-Shot surface mount speakers. Each feature flame retardant housing material and a tuned PA driver to suit the new approval requirements. One-Shot design simply snap-fits in seconds to the surface mounting ring, reducing installation time considerably. The C 0713 adaptor plate enables the surface mounting ring to be fixed to a standard conduit junction box without the need for drilling into the slab.

**SPECIFICATIONS**

Power taps: 0.33, 0.66, 1.25, 2.5, 5W  
 SPL 1W @ 1m: 93dB @ 1kHz ±2dB  
 Terminal type: 4 way screw terminal & 22µF bipolar cap



C 0713 fitted to mounting ring.

Price Each	RRP	4+	10+
<b>CF0715</b> 5 Watt White	<b>95.00</b>	<b>85.00</b>	<b>77.00</b>
<b>CF0716</b> 5 Watt Black	<b>104.50</b>	<b>93.50</b>	<b>84.70</b>
<b>C 0713</b> Adaptor plate for conduit boxes	<b>9.50</b>	<b>8.70</b>	<b>7.65</b>

See page 114 for vandal resistant cage to suit C 0703-4 and CF0703-4 100mm surface mount speakers.